


















Caratteristiche *Characteristics*

Tipo di installazione	<i>Type of installation</i>	Parete/Soffitto/Sospensione	<i>Wall/ ceiling / pendant</i>
Materiale	<i>Material</i>	Alluminio	<i>Aluminum</i>
Finitura	<i>Finish</i>	Alluminio anodizzato	<i>Anodized aluminum</i>
Dimensioni	<i>Dimensions</i>	40mm x 50mm. L. 3000 mm max	

Accessori *Accessories*

<p>Cover opalina bianca PMMA <i>Diffuser opal white PMMA</i> G100062398961</p> 	<p>Cover satinata PMMA <i>Diffuser satined PMMA</i> G100062398971</p> 	<p>Cover prisma PMMA <i>Diffuser prisma PMMA</i> G100062399681</p> 	<p>Diffusore opalino, PMMA 180° <i>Diffuser opal, PMMA, 180°</i> G100062399661</p> 	<p>Diffusore opalino semi circolare <i>Semi-circular diffuser, opal</i> G100062399621</p> 
<p>Cover trasparente PMMA <i>Diffuser clear PMMA</i> G100062398951</p> 	<p>Cover alluminio anodizzato <i>Diffuser anodized aluminum</i> G100062399671</p> 	<p>Inserto 4050 per STRIP-LED <i>4050 insert profile</i> G100062399651</p> 	<p>Set di staffe in aisi <i>Bracket set in stainless steel</i> G100062399906</p> 	
<p>Set di staffe in aisi 90° <i>Angle Bracket set, stainless steel</i> G100062398801</p> 	<p>Connettore lineare in metallo <i>Profile connector, metal.</i> G100062399919</p> 	<p>Connettore a 90° in metallo <i>Profile connector 90°, metal.</i> G100062399936</p> 	<p>Connettore regolabile <i>Adjustable connector</i> G100062398806</p> 	
<p>Tappi in plastica per 180° <i>Aluminum end caps 180°</i> G100062399648</p> 	<p>Tappo in alluminio <i>End cap, aluminum</i> G100062399646</p> 	<p>Tappo in alluminio <i>End cap, aluminum</i> G100062399627</p> 	<p>Tappo in alluminio <i>End cap, aluminum</i> G100062399647</p> 	<p>Kit sospensione <i>Pendant kit</i> G100065400100</p> 